

INDUSTRIAL STEAM GENERATOR

- Car Washes & Detail shops
- Auto Dealerships
- Transportation
- Industrial and mechanical environments in general



Steamy 10
1 output at 10 bar

Steamy 10 SH
1 output at 10 bar
with detergent pump



Steamy 10		
code	Volt -Hz	A
Q80001868	208-60 3 phases	28
Q80002108	230-60 3 phases	25
Q80006021	400-50 3 phases	15
Q80001881	440-60 3 phases	13
Q80001698	575-60 3 phases	10

Steamy 10 SH		
code	Volt -Hz	A
Q80001861	208-60 3 phases	28
Q80002109	230-60 3 phases	25
Q80006022	400-50 3 phases	15
Q80001874	440-60 3 phases	13
Q80001691	575-60 3 phases	10

accessories

for 208 V, 230 V, 440 V and 575 V accessories included - see table **B1**

for 400 V accessories not included - see tables **A1-A4**

	measure units	Steamy 10	Steamy 10 SH
start up time	min	7	7
boiler capacity	liter/gallon	6,6/1,74	6,6/1,74
boiler material	type	AISI 304	AISI 304
boiler power	kW	10	10
boiler temperature regulation	yes/no	no	no
steam production	g/min	260	260
steam output regulation	type	no	no
working pressure	bar/psi	10/145	10/145
steam temperature in boiler	°C/°F	185/365	185/365
water output regulation	yes/no	no	no
water output	yes/no	yes	no
detergent output	yes/no	no	yes
water tank capacity	liter/gallon	11/2,91	11/2,91
unlimited autonomy	yes/no	yes	yes
detergent tank capacity	liter/gallon	11/2,91	11/2,91
machine body material	type	metal-painted	metal-painted
weight net	kg/lbs	75/166	79/174
machine dimension	l x p x h cm	74x58x97	74x58x97
packaging dimension	l x p x h cm	85x65x121	85x65x121
packaging weight	kg/lbs	117/258	121/267
packaging box	type	wooden	wooden
vacuum cleaner	yes/no/optional	no	no
waste water tank capacity	liter/gallon	-	-
vacuum power	kW	-	-
vacuum	kPA	-	-
vacuum filter	type	-	-
wet & dry	yes/no	-	-

General Vapeur S.r.l.

Headquarters: Strada per Castelletto 19/21 - 20080 Albairate (MI) - Italy
Phone: +39.02.94981104 • Fax: +39.02.94981134
infoclienti@menikini.com • www.menikini.com • C.S. € 1.800.000

 **menikini**[®]
industrial sanitizing
with ecological dry steam

INDUSTRIAL STEAM GENERATOR

- **Car Washes & Detail shops**
- **Auto Dealerships**
- **Transportation**
- **Industrial and mechanical environments in general**

STEAMY 10-6 DUPLEX

1 output at 10 bar
1 output at 6 bar

STEAMY 10-6 DUPLEX SH

1 output at 10 bar
with detergent pump
1 output at 6 bar
with detergent pump

STEAMY 10-10 SH

2 output at 10 bar
with detergent pump

accessories

for 208 V, 230 V, 440 V
and 575 V accessories
included - see table **B1**
ONE SET FOR 1 EXIT

for 400 V accessories not
included - see tables **A1-A4**

for 6 bar output see table **7&3**



Steamy 10-6 duplex			measure units	Steamy 10-6 duplex	Steamy 10-6 duplex SH	Steamy 10-10 SH
code	Volt -Hz	A				
Q80001869	208-60 3 phases	28	start up time	min	7	7
Q80002111	230-60 3 phases	25	boiler capacity	liter/gallon	6,6/1,74	6,6/1,74
080006023	400-50 3 phases	15	boiler material	type	AISI 304	AISI 304
Q80001882	440-60 3 phases	13	boiler power	kW	10	10
Q80001699	575-60 3 phases	10	boiler temperature regulation	yes/no	yes	no
Steamy 10-6 duplex SH			steam production	g/min	260	260
code	Volt -Hz	A	steam output regulation	type	manual only on 6 bar	manual only on 6 bar
Q80001862	208-60 3 phases	28	working pressure	bar/psi	10/145 - 6/87	10/145 - 6/87
Q80002112	230-60 3 phases	25	steam temperature in boiler	°C/°F	185/365 - 165/329	185/365 - 165/329
080006024	400-50 3 phases	15	water output regulation	yes/no	no	no
Q80001875	440-60 3 phases	13	water output	yes/no	yes	no
Q80001692	575-60 3 phases	10	detergent output	yes/no	no	yes
Steamy 10-10 SH			water tank capacity	liter/gallon	11/2,91	11/2,91
code	Volt -Hz	A	unlimited autonomy	yes/no	yes	yes
Q80001863	208-60 3 phases	28	detergent tank capacity	liter/gallon	11/2,91	11/2,91
Q80002110	230-60 3 phases	25	machine body material	type	metal-painted	metal-painted
080006025	400-50 3 phases	15	weight net	kg/lbs	76/167	80/177
Q80001876	440-60 3 phases	13	machine dimension	l x p x h cm	74x58x97	74x58x97
Q80001693	575-60 3 phases	10	packaging dimension	l x p x h cm	85x65x121	85x65x121
			packaging weight	kg/lbs	118/260	122/269
			packaging box	type	wooden	wooden
			vacuum cleaner	yes/no/optional	no	no
			waste water tank capacity	liter/gallon	-	-
			vacuum power	kW	-	-
			vacuum	kPA	-	-
			vacuum filter	type	-	-
			wet & dry	yes/no	-	-



General Vapeur S.r.l.

Headquarters: Strada per Castelletto 19/21 - 20080 Albairate (MI) - Italy
Phone: +39.02.94981104 • Fax: +39.02.94981134
infoclienti@menikini.com • www.menikini.com • C.S. € 1.800.000

menikini[®]
industrial sanitizing
with ecological dry steam

Steamy



leader in **dry steam** technology

INDUSTRIAL STEAM GENERATOR

- Car Washes & Detail shops
- Auto Dealerships
- Transportation
- Industrial and mechanical environments in general



STEAMY 10-6 DU SH VAC

1 output at 10 bar with detergent pump
1 output at 6 bar with detergent pump
1 vacuum cleaner

STEAMY TRIO VAC

2 output at 10 bar with detergent pump
1 output at 6 bar with detergent pump
1 vacuum cleaner



Steamy 10-6 DU SH VAC		
code	Volt -Hz	A
Q80001864	208-60 3 phases	28
Q80002113	230-60 3 phases	25
080006026	400-50 3 phases	15
Q80001877	440-60 3 phases	13
Q80001694	575-60 3 phases	10

Steamy trio VAC		
code	Volt -Hz	A
Q80001870	208-60 3 phases	28
Q80002114	230-60 3 phases	25
080006155	400-50 3 phases	15
Q80001883	440-60 3 phases	13
Q80001777	575-60 3 phases	10

accessories

for 208 V, 230 V, 440 V and 575 V accessories included - see table **B1**
ONE SET FOR 1 EXIT

for 400 V accessories not included - see tables **A1-A4**

for 6 bar output see table **7**

	measure units	Steamy 10-6 DU SH VAC	Steamy trio VAC
product code		080006026	080006155
power supply	V-Hz	400-50*	400-50*
total power	kW	10 + 1	10 + 1
power absorption	A	15+6	15+6
start up time	min	7	7
boiler capacity	liter/gallon	6,6/1,74	6.6/1,74
boiler material	type	AISI 304	AISI 304
boiler power	kW	10	10
boiler temperature regulation	yes/no	yes	yes
steam production	g/min	260	260
steam output regulation	type	manual only on 6 bar	manual only on 6 bar
working pressure	bar/psi	10/145 - 6/87	10/145 - 6/87
steam temperature in boiler	°C/°F	185/365 - 165/329	185/365 - 165/329
water output regulation	yes/no	no	no
water output	yes/no	no	no
detergent output	yes/no	yes	yes
water tank capacity	liter/gallon	11/2,91	11/2,91
unlimited autonomy	yes/no	yes	yes
detergent tank capacity	liter/gallon	11/2,91	11/2,91
machine body material	type	metal-painted	metal-painted
weight net	kg/lbs	81,5/178	82,5/181
machine dimension	l x p x h cm	101x58x97	101x58x97
packaging dimension	l x p x h cm	85x65x170	85x65x170
packaging weight	kg/lbs	140/308	140/308
packaging box	type	wooden	wooden
vacuum cleaner	yes/no/optional	yes	yes
waste water tank capacity	liter/gallon	15/3,96	15/3,96
vacuum power	kW	1	1
vacuum	kPA	24	24
vacuum filter	type	Polyester	Polyester
wet & dry	yes/no	yes	yes

General Vapeur S.r.l.

Headquarters: Strada per Castelletto 19/21 - 20080 Albairate (MI) - Italy
Phone: +39.02.94981104 • Fax: +39.02.94981134
infoclienti@menikini.com • www.menikini.com • C.S. € 1.800.000

menikini[®]
industrial sanitizing
with ecological dry steam